



DSL-X25 SERIES

LED MINI FLASHING LAMP



PRODUCT BENEFITS

- Available in Blue, Red and Amber emitted light
- Designed with high level Electromagnetic Compatibility (EMC) specifications
- Compact and lightweight design
- Asynchronous and Synchronous patterns
- Multivoltage 10-30V
- IP69K

FUNCTIONS LAYOUT



TECHNICAL SPECIFICATIONS

TECHNICAL DATA

Variants	Series DSL-X25.05	Series DSL-X25.06	Series DSL-X25.08	
Operating Voltage	10 V - 30 V			
Reverse Polarity Protection	Yes			
Light Function	LED Warning Light			
Emitted Color	Amber	Red	Blue	
Consumption	6.3 W	6.2 W	9 W	
Temperature Range	- 40°C to + 65°C			
Type of Mounting	Screw Mounting			
Material	Lens	PC		
	Housing	ADC12		
Type of Protection	IP69K			
Approvals	ECE	R65	R65	R65
		XA1	XR1	XB1
	EMC	00	00	00
Flashing Patterns	10			
	The products are equipped with either synchronous and/or asynchronous functions			
Type of Connection	500mm Cable			

CODES OVERVIEW

Variants Ref. No.	Amber	Red	Blue	Synch	Synch & Asvnch
DSL-X25.05	•				•
DSL-X25.06		•			•
DSL-X25.08			•		•

DIMENSIONAL DRAWING

